

(21) Application No 9215558.9

(22) Date of filing 22.07.1992

(30) Priority data

(31) 755932

(32) 06.09.1991

(33) US

(71) Applicant  
Motorola Inc

(Incorporated in the USA - Delaware)

Corporate Offices, 1303 East Algonquin Road,  
Schaumburg, Illinois 60196, United States of America(72) Inventors  
Robert F D'Avello  
Manohar A Joglekar(74) Agent and/or Address for Service  
Hugh Christopher Dunlop  
Motorola Limited, European Intellectual Property  
Operations, Jays Close, Viabes Industrial Estate,  
Basingstoke, Hampshire, RG22 4PD, United Kingdom(51) INT CL<sup>5</sup>  
H04Q 7/04(52) UK CL (Edition L)  
H4L LECX  
U1S S2210(56) Documents cited  
GB 2240904 A EP 0361350 A2 US 4837590 A(58) Field of search  
UK CL (Edition K) H4K KOD2 KOD8 KYR KYX, H4L  
LECX  
INT CL<sup>5</sup> H04M, H04Q  
Online databases: WPI.

(54) Data communication system with automatic power control

(57) A communication system comprised of a transceiver (101) for transmitting and receiving data signals and a modulation/demodulation apparatus (102) to modulate the data signals from an accessory (109) for transmission and demodulate data signals after reception by the transceiver (101). A processing device (103) controls power to the various components of the communication system so that they are only powered when in use, thus saving the power sources of the respective accessories.




FIG. 1






FIG. 1

*FIG. 2A*

*FIG. 2B*

## DATA COMMUNICATION SYSTEM WITH AUTOMATIC POWER CONTROL

### Field of the Invention

5

The present invention relates generally to the field of communications and particularly to automatic power control of a communication system.

10

### Background of the Invention

15

20

A radiotelephone/facsimile combination allows a user to transmit and receive documents without having the constraints of a fixed office. A radiotelephone/computer combination permits a computer user to access a data base or to contact other computer users with a portable computer, also without being tied down to an office. If the computer has the proper modem, documents can also be sent from the computer to a facsimile machine. A typical radiotelephone is described in detail in Motorola Micro T-A-C manual #68P81150E49 available from the assignee of the present invention.

25

30

35

The problem with these schemes, however, is that these combinations are typically powered by a car's electrical system. To remain truly mobile, the radiotelephone/facsimile or radiotelephone/computer must be battery powered, allowing the user to take the combinations anywhere. This results in the combinations being powered by either one battery for both units of the combination or separately powering each unit with separate batteries, requiring a larger and heavier combination. With either power scheme, both units of the combination must either remain powered up to receive an incoming call or the facsimile or computer turned on manually when a telephone call is received that requires those units. In either case, the battery's usefulness will decrease due to the time the units are on and not being used. Even if the units are turned on and off manually when a call is received, there is still the

possibility of it being inadvertently left on and draining the battery.

A radiotelephone/computer user may also want to send data out via a modem that is connected to the radiotelephone.

5 In this case the radiotelephone must be left on or turned on and off manually when it is needed. There is a resulting need for a radiotelephone/computer or radiotelephone/facsimile combination that conserves battery power when not active.

## 10 **Summary of the Invention**

The communication system of the present invention is comprised of transceiving means for transmitting and receiving data signals and modulation/demodulation means to  
15 modulate/demodulate the data signals for transmission and after reception. Processing means controls the operation of the communication system.

## **Brief Description of the Drawings**

20

FIG. 1 shows a block diagram of the data communication system.

FIGs. 2A and B show flow diagrams of the process used by the controller of the communication system.

25

## **Detailed Description of the Preferred Embodiment**

The data communication system utilizes a bidirectional power controller that controls power to a radiotelephone and  
30 facsimile machine, computer, or other accessory coupled to the radiotelephone. Thus, when an accessory is needed, power to that accessory is enabled.

The preferred embodiment of the data communication system is illustrated in FIG. 1. The system is comprised of a  
35 microprocessor or microcontroller (103) (hereinafter referred to as the controller) to control the system. The controller (103)

controls power switches (106 - 108) to an external accessory (computer, facsimile machine, etc.) (109), as well as to the modem (102) and radiotelephone (101), as required by the process of the present invention, illustrated in FIGs. 2A and B.

5 The power control switches (106, 108) to the accessory and the radiotelephone are coupled to ground while the switch (107) to the modem is coupled to the radiotelephone's battery or other power source.

10 The external accessory (109) communicates commands and data to the controller (103) via an asynchronous communications interface adapter (ACIA) (104). The controller (103) communicates commands and data to the modem (102) via another ACIA (111). If the external accessory (109) communicates over an RS-232 bus, a level  
15 translator (105) can be used to convert the RS-232 logic levels to TTL levels.

The radiotelephone (101) is coupled to the modem (102) by the radiotelephone's audio line (110). The modem (102) can then transmit or receive modulated data through the ra-  
20 diotelephone's transmitter or receiver. In the preferred embodiment, the radiotelephone's battery powers the modem (102). The battery is coupled to the modem (102) through a power control switch (107).

Referring to FIG. 2B, the radiotelephone is normally in  
25 a low-power stand-by mode when turned on and not in use (201). The accessory, if not being used, is off or also in a low-power stand-by mode (201). The modem is off (201). When a call is received from a base station (202), the radiotelephone goes into an active mode to receive the call. The call is indi-  
30 cated by a received ring signal that is also coupled to the controller. The controller, in response to this ring signal, turns on the accessory and the modem and the call is answered by the radiotelephone (203). Data is then received from the transmitting party. In one embodiment of the present  
35 invention, the controller can return the components of the system to their previous state of power (204).

If the accessory originates a command (205), the command is executed by the controller (206). An example of such a command is for the data communication system to originate a data transfer.

5        This data transfer process is illustrated in FIG. 2A. For this embodiment of the process, the accessory is on while the modem is off and the radiotelephone is off or in the stand-by mode. The accessory sends a command to the controller (220). If the controller determines the command is a power  
10    control command (221), the command is executed by the controller (223), e.g., the controller turns on the radiotelephone and modem. If the radiotelephone was already on and in the stand-by mode, the transmission of data will cause it to go into the active mode.

15        If the controller determines the command is to retrieve radiotelephone data (224), the controller turns on the radiotelephone if it was off and retrieves the data (225). This data could include received signal strength information (RSSI) or data from the radiotelephone's memory (i.e., tele-  
20    phone numbers).

      If the controller determines the command is intended for the modem's intelligent controller (222), the controller turns on the modem and passes the command to the modem's controller (226). An example of such a command is the "AT"  
25    dial command. The modem's controller can then transfer the telephone number, attached to the command, to the radiotelephone for dialing. The accessory can now communicate, through the modem and radiotelephone, to another accessory that is using either a radiotelephone or a landline telephone  
30    and a modem.

      If the accessory (109) is a computer, a data modem can be used. An example of such a modem is a UDS V.22bis. If the accessory (109) is a facsimile machine, a facsimile modem can be used. An example of such a modem is a Worldport  
35    2496.



Once the call has been completed, the controller (103) removes power from the modem (102) and the radiotelephone (101). The accessory (109) is powered down by its own internal power-down algorithm. An alternate embodiment powers  
5 down the modem and radiotelephone automatically a predetermined time after the call has ended. Another alternate embodiment would power down the modem and radiotelephone a predetermined time after the last command has been sent from the accessory to the apparatus, if the radiotelephone  
10 is not in a call. Yet another embodiment would complete the power down procedure only after a command was sent from the computer instructing the power down to occur. Another embodiment could use the controlling controller to power-down the accessory after transfer of the data.

15 The data communication system can be built into the accessory (109). In alternate embodiments, the items of the communication system can be in separate enclosures or share the same enclosures. Also in alternate embodiments, all the components of the present invention can share the same  
20 power source or be combined in various combinations.

The data communication system described reduces the time a battery needs to power a modem combined with a radiotelephone by turning off both components when not needed. By reducing the time these components are drawing  
25 power, the battery use can be greatly extended.

Claims

1. A communications system for transferring data signals to  
and from an accessory that generates a first power control  
5 signal, the system comprising:  
transceiver means for transmitting and receiving the  
data signals and for generating a second power control signal;  
modulation/demodulation means, coupled to the  
transceiver means and to the accessory, for demodulating re-  
10 ceived data signals and modulating data signals from the ac-  
cessory; and  
processing means, for controlling power to the  
transceiver means, the modulation/demodulation means, and  
the accessory, in response to the first and second power con-  
15 trol signals.

2. The system of claim 1 wherein the accessory is means for computing.
3. The system of claim 1 wherein the accessory is a facsimile machine.
- 5 4. The system of claim 1 wherein the modulation/ demodulation means is a modem.

5. A communications system for communicating data signals, the system having a power input, the system comprising:

5       computing means, for generating a first power control signal and the data signals;

      transceiver means for transmitting and receiving the data signals and generating a second power control signal;

      modulation/demodulation means, coupled to the transceiver means and the computing means, for demodulating received data signals from the transceiver means and modulating data signals from the computing means; and

10       controller means, coupled to the transceiver means, the modulation/demodulation means, and the computing means, for controlling power to the modulation/demodulation means in response to the first or the second power control signals, controlling power to the transceiver means in response to the first power control signal, or controlling power to the computing means in response to the second power control signal.

6. A communications system for communicating data signals, the system having a power input, the system comprising:

5 facsimile means, for generating a first power control signal and the data signals;

transceiver means for transmitting and receiving the data signals and generating a second power control signal;

10 modulation/demodulation means, coupled to the transceiver means and the facsimile means, for demodulating received data signals from the transceiver means and modulating data signals from the facsimile means; and

15 controller means, coupled to the transceiver means, the modulation/demodulation means, and the facsimile means, for controlling power to the modulation/demodulation means in response to the first or the second power control signals, controlling power to the transceiver means in response to the first power control signal, or controlling power to the facsimile means in response to the second power control signal.

**Patents Act 1977**  
**Examiner's report to the Comptroller under**  
**Section 17 (The Search Report)**

-10-  
Application number

GB 9215558.9

**Relevant Technical fields**

(i) UK Cl (Edition K ) H4L (LECX); H4K (KYR, KYX,  
KOD2, KOD8)

(ii) Int Cl (Edition 5 ) H04M, H04Q

**Search Examiner**

MR S J L REES

**Databases (see over)**

(i) UK Patent Office

(ii) ONLINE DATABASES: WPI

**Date of Search**

20 OCTOBER 1992

Documents considered relevant following a search in respect of claims

ALL CLAIMS

Category (see over)	Identity of document and relevant passages	Relevant to claim(s)
A	GB 2240904 A (OKI) whole document	1, 3, 5, 6
A	EP 0361350 A2 (NEC) whole document	1-6
A	US 4837590 (SPRAQUE) whole document	1, 2, 4, 5

Category	Identity of document and relevant passages	Relevant to claim(s)

### Categories of documents

**X:** Document indicating lack of novelty or of inventive step.

**Y:** Document indicating lack of inventive step if combined with one or more other documents of the same category.

**A:** Document indicating technological background and/or state of the art.

**P:** Document published on or after the declared priority date but before the filing date of the present application.

**E:** Patent document published on or after, but with priority date earlier than, the filing date of the present application.

**&:** Member of the same patent family, corresponding document.

**Databases:** The UK Patent Office database comprises classified collections of GB, EP, WO and US patent specifications as outlined periodically in the Official Journal (Patents). The on-line databases considered for search are also listed periodically in the Official Journal (Patents).

**This Page Blank (uspto)**